



C-TEC
 'BUILDING PRODUCT
 SPECIALISTS'

PRODUCT - INFO

CT Roof



C T Roof is a sealant with a unique composition. Due to the combination of bitumes, butyl rubber and glass fibres, a product with a very high tensile strength and flexibility is obtained. Therefore, a life span of 20 years is guaranteed for C T Roof.

C T Roof can be applied on most surfaces, also in a moist condition.

INSTRUCTIONS FOR USE

1. The Surface has to be solid and clean.
2. Remove loose parts and hardened bitumes.
3. Cut open blisters in roofing materials in a cross shaped way.
4. Larger repairs have to be reinforced with pieces of roofing or glass fibre tissue.
5. Apply with a cartridge gun, brush or spatula.
6. Finish off and clean tools with Multisolve

APPLICATIONS

C T ROOF can be applied on most building materials such as brick, concrete, wood, lead, copper, tin
 Bituminous roofing materials, galvanized steel, insulation materials, PVC, polyester.

Typical applications:-

- All types of roof repairs: sloping and flat roofs, roof gutters, edgings, drain pipes, lead flashings, corrugated plates, also on wet surfaces.
- Sealing and finishing off of roof joints, eaves, feed-through ducts, chimneys.
- As cold adhesive for roof repairs with bituminous roofing materials.
- Making waterproof of concrete and brickwork in foundations and terraces.
- Corrosion protection of underground pipelines and channels.

Technical

Composition	Modified bitumes, glass Fibres and butyl rubber
Elongation at rupture (dry film)	170%
Temperature resistance	-45°C to +85°C
U.V. resistance	excellent
Aging properties.	none during 20 years
Water resistance	very good in case of a normal draining
Climatic resistance	excellent
Resistance to hydrocarbons	not resistant
Application temperature	-12°C to +50°C
	DO NOT APPLY ON SNOW OR GLAZE ICE!!